
TEFCOLD®
COOL PRODUCTS WORLDWIDE



EIB-D1010-B1


Black impulse cooler/freezer

Product Features
- Easily switchable between cooler and freezer
- Temperature Class 3M1/3L1
- Glass sides for better presentation of products
- Ventilated cooling
- LED interior light
- Sliding glass lids
- Ticket strip included
- Stainless steel bumper bars on all four sides
- Controller with Bluetooth and NFC connectivity
- Castors, 2 lockable
- HACCP compliant data export

Versatile impulse chiller/freezer

The EIB mobile chiller/freezer from TEFCOLD is an adaptable solution, ideal for UK retail environments. Designed with flexible cooling and freezing options, generous storage capacity, and a strikingly elegant appearance, this unit is perfect for promoting impulse buys. Easily switch between cooling and freezing modes according to your requirements. It meets temperature class 3M1/3L1 standards, making it well-suited for retail use. The unit features interior LED lighting and four glass sides with sliding lids, ensuring excellent product visibility that entices customers. Fitted with castors and brakes, it can be conveniently moved and positioned for optimal impact. Available in various sizes, this impulse merchandiser is a valuable addition to any retail space.

Measures and Content		
Gross / Net Weight	kg	229 / 204
Gross / Net Volume	l	320 / 213
Total Display Area	m²	1.59
Temperature Range	°C	-18 to +5
Climate Class		3
Design and Material		
Exterior Finish		Black RAL9005
Interior Finish		Black (RAL9005)
Number of lids		2
Lid Number & Type		2 flat sliding glass lid
Tempered glass		Yes
Castors		Wheels
Interior Light		LED Horizontal
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	110
Thermometer		Yes
Power and Consumption		
Energy Class		C
Max Ambient		+25°C, 60% RH
Energy Consumption	kWh/24h	7.83
Annual Energy Consumption	kWh/year	2857.95
EEI	%	34.9
Input Power	W	1231
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	54
Dimensions		
External Dimension (WxDxH)	mm	1012 x 1010 x 975
Internal Dimension (WxDxH)	mm	860 x 790 x 300
Packed Dimension (WxDxH)	mm	1070 x 1070 x 1155
40ft Container Load	pcs	40


Strong handle


Digital controller