

BA26H

Backbar Cooler

Product Features

- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- Ventilated cooling for fast pull-down and even temperature
- Energy saving variable speed compressor
- Double glazed tempered glass
- Hinged alu-framed glass doors
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light
- Lock

High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat. The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has hinged aluminium doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility. The BA range is also available in a variant with self-closing sliding doors.

Measures and Content

Total Display Area	m ²	0.5
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	69 / 63
Gross Volume	l	190
Gross / Net Volume	l	190 / 182

Design and Material

Door No & Type	2 hinged glass doors	
Door Reversible	No	
Tempered glass	Yes	
Shelves No & Type	4 wire shelves chrome	
Shelf Color	Chrome	
Shelf Dimensions	395x328 mm	
Feet / Legs	4 adjustable feet	
Exterior Finish	Black	
Interior Finish	Stucco aluminium	
Interior Light	LED	
Lock	Yes	

Cooling and Functions


Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R600a	
Refrigerant Charge	g	70
Thermometer	Yes	

Power and Consumption

Energy Class	A	
Max Ambient	30°C at 55% RH	
Energy Consumption	kWh/24h	1.08
Annual Energy Cons.	kWh/year	394
Power	13 Amp	
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

Dimensions

Internal Dimension (WxDxH)	mm	810 x 418 x 720
External Dimension (WxDxH)	mm	900 x 520 x 870
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96



Adjustable wire shelves



Electronic thermostat