



## CRNF1830

Coldroom (Freezing)

### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

### Measures and Content

Internal Volume	m³	8.44
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	715 / 685
Gross / Net Volume	l	

### Design and Material

Door Number & Type	1 hinged solid door W:700 H:1765	
Max Load on Floor	kg/m²	2000
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	

### Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	200
Thermometer	Yes	

### Power and Consumption

Max Ambient	40°C at 40% RH	
Energy Consumption	kWh/24h	29.52
Annual Energy Consumption	kWh/year	10775
Power	13 Amp	
Input Power	W	1394.73
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

### Dimensions

Internal Dimension (WxDxH)	mm	1560 x 2760 x 1960
External Dimension (WxDxH)	mm	1800 x 3000 x 2200
Packed Dimension (WxDxH)	mm	2200 x 1900 x 2400
40ft Container Load	pcs	6



Strong handle



Shelf as accessory