



WRA-M5-1

Monoblock Cooler Unit

Product Features

- Monoblock cooling unit
- Suitable for panels up to 200 mm thick
- Serial connection possible
- Digital controller and temperature display
- Ventilated cooling

Monoblock cooling unit for temperature -5°C to +15°C

The WRA monoblock cooling unit delivers exceptional refrigeration performance for cold rooms. The monoblock is designed for saddle mounting and installation requires cutting holes in the cold room panels. The monoblock is suitable for all panels with a depth of up to 200 mm.

You can see the capacity of the monoblock in the drawings. The performance depends on different factors such as ambient temperature and setpoint temperature.

If you have a larger cold room, it is possible to connect several monoblocks and have them operate together. You choose one unit to be the master and control the temperature for all units on just one controller.

The monoblock is for indoor use only.

Measures and Content

Gross / Net Weight	kg	54 / 42
Temperature Range	°C	-5 to +15

Design and Material

Exterior Finish	White RAL9003
-----------------	---------------

Cooling and Functions

Type of Controller	Electronic
Type of Defrost	Automatic, hot gas
Refrigerant	R290
Refrigerant Charge	g150
Thermometer	Yes

Power and Consumption


Energy Consumption	kWh/24h	6.48
Annual Energy Cons.	kWh/year	2365
Input Power	W	360
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	31.1

Dimensions

External Dimension (WxDxH)	mm	421 x 876 x 728
Packed Dimension (WxDxH)	mm	500 x 970 x 890
40ft Container Load	pcs	52



Monoblock rear – no panel attached



Digital controller