



LGF2500B

Display Freezer

Product Features

- LED illuminated canopy
- Heated glass to help prevent condensation
- Self closing doors with stay open feature for easy loading
- Adjustable shelves
- Digital controller and temperature display
- LED interior light with switch
- Internal stainless steel base
- Ventilated cooling
- Automatic defrost
- Castors and locking feet

Elegant black display freezer with canopy

The LGF-B display freezer is designed to integrate effortlessly into your retail or catering setting, adding a touch of elegance and quality with its stylish black finish. It features two vertical LED light strips on each door, which highlight the contents inside with an eye-catching contrast against the dark interior. Moreover, an LED illuminated canopy tops the unit, providing an outstanding opportunity for customized branding and promotional displays. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. The carefully engineered refrigeration system is highly energy-efficient, reducing costs while maintaining the ideal temperature for product freshness. For added convenience, the unit includes castors, making it easy to move for cleaning and repositioning as needed.

Measures and Content

Gross / Net Weight	kg	140 / 120
Net Volume	l	405
Gross Volume	l	496
Gross / Net Volume	l	496 / 405
Total Display Area	m²	0.69
Temperature Range	°C	-25 to -14
Climate Class		4

Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Black
No. of Doors		1
Door No & Type		1 hinged glass door
Door Reversible		No
No. of Shelves	pcs	4
Shelves No & Type		4
Shelf Dimensions		545*622
Interior Light		2 x Vertically LED in door frame

Cooling and Functions

Type of Cooling		Ventilated
Type of Defrost		Automatic, electric
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes

Power and Consumption

Energy Class		C
Energy Consumption	kWh/24h	7.79
Annual Energy Cons.	kWh/year	2842
EEl	%	34
Power Supply		13 Amp
Input Power	W	650
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	59

Dimensions

External Dimension (WxDxH)	mm	685 x 805 x 2065
Internal Dimension (WxDxH)	mm	565 x 640 x 1520
Packed Dimension (WxDxH)	mm	745 x 860 x 2210
40ft Container Load	pcs	44



Illuminated canopy



Strong castors