



KBAK104

Bottle Dump Cooler

Product Features

- Low energy consumption
- Impressive storage space
- Removable top for easy loading
- Ideal for storing beer and soft drink crates
- Flat solid sliding lids
- Solid castors
- Static cooling

Chest bottle cooler

The KBAK chest bottle cooler has been designed to cater to your bulk storage needs and facilitate rapid drinks service. It optimizes storage space by positioning the refrigeration compartment at the unit's base, to give the storage area a completely flat base with no internal step. With insulated sliding lids, you can effortlessly access stock ensuring swift and efficient service. Ideal for bustling bars, nightclubs, event venues, and festivals. The PLUS variation is equipped with heavy duty and protective bumper bars. Both units have the ability to remove the sliding lids and stack the coolers for storage and transportation, making them a versatile choice for rental and event companies, as well as mobile bars.

Measures and Content

| | | |
|--------------------|----|-----------|
| Temperature Range | °C | +1 to +8 |
| Climate Class | | 4 |
| Net Volume | l | 226 |
| Gross Volume | l | 250 |
| Gross / Net Volume | l | 250 / 226 |
| Gross / Net Weight | kg | 70 / 60 |

Design and Material

| | |
|-------------------|----------------------|
| Number of lids | 2 |
| Lid Number & Type | 2 solid sliding lids |
| Castors | Wheels |
| Interior Light | No |
| Lock | Factory Option |
| Exterior Finish | White |
| Interior Finish | White |

Cooling and Functions

| | | |
|--------------------|------------|----|
| Type of Controller | Mechanical | |
| Type of Cooling | Static | |
| Type of Defrost | Manual | |
| Refrigerant | R600a | |
| Refrigerant Charge | g | 34 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------------|---------------|------------|
| Energy Class | B | |
| Max Ambient | +30°C, 55% RH | |
| Annual Energy Consumption | kWh/year | 198 |
| Energy Consumption | kWh/24h | 0.54 |
| EEL | % | 14 |
| Power | 13 Amp | |
| Input Power | W | 190 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |

Dimensions

| | | |
|----------------------------|-----|-------------------|
| External Dimension (WxDxH) | mm | 1025 x 625 x 1000 |
| Internal Dimension (WxDxH) | mm | 900 x 500 x 555 |
| Packed Dimension (WxDxH) | mm | 660 x 1100 x 1060 |
| 40ft Container Load | pcs | 72 |



Strong castors



Easy access storage compartment