



EXTRA1875FD

Supermarket Multideck Freezer

Product Features

- Can be multiplexed - Create uninterrupted continuous line
- Temperature Class 3L1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Solid end walls as standard
- Multiplexing kit as accessory

Full Class Door Multideck Freezer with Multiplexing Opti

EXTRA Multideck is a premium full glass door freezer with double glazed hinged glass doors for added energy efficiency savings on running costs. For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Wire shelving with ticket strips and shelf risers are supplied as standard. Installation is simple and quick. No special requirements as refrigerant charge is below 150g. The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Measures and Content

Total Display Area	m ²	2.72
Temperature Range	°C	-21 to -18
Climate Class		3
Gross / Net Weight	kg	490 / 440
Gross / Net Volume	l	1350 / 1270

Design and Material

Door No & Type		3 hinged glass doors
Tempered glass		Yes
Door Reversible		No
Shelves No & Type		12 wire shelves black
Shelf Color		Black
Max load on Shelves	kg/m ²	150
Feet / Legs		6 adjustable feet
Castors		Option
Exterior Finish		Black / Glass
Interior Finish		Black
Interior Light		2 x Vertically LED
Lock		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	2x144
Thermometer		Yes

Power and Consumption

Energy Class		E
Energy Consumption	kWh/24h	34.76
Annual Energy Cons.	kWh/year	12687
Input Power	W	1860
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	53

Dimensions

Internal Dimension (WxDxH)	mm	1875 x 610 x 1399
External Dimension (WxDxH)	mm	1975 x 930 x 2035
Packed Dimension (WxDxH)	mm	2075 x 975 x 2230
40ft Container Load	pcs	12



Extraordinary space on shelves

Electronic thermostat