




ECO-FRIENDLY  
REFRIGERANT R290



## CRPF1521

### Chiller Room

#### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

#### Measures and Content

Internal Volume	m³	5.3
Wall Thickness	mm	80
Insulation Density	kg/m³	42
Temperature Range	°C	0 to +8
Climate Class		5
Gross / Net Weight	kg	321 / 291
Gross / Net Volume	l	

#### Design and Material

Door Number & Type	1 hinged solid door W:700 H:1845	
Max Load on Floor	kg/m²	1500
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	

#### Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	130
Thermometer	Yes	

#### Power and Consumption

Max Ambient	40°C at 40% RH	
Energy Consumption	kWh/24h	18.72
Annual Energy Consumption	kWh/year	6833
Power	13 Amp	
Input Power	W	860
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

#### Dimensions

Internal Dimension (WxDxH)	mm	1340 x 1940 x 2040
External Dimension (WxDxH)	mm	1500 x 2100 x 2200
Packed Dimension (WxDxH)	mm	2200 x 1300 x 2400
40ft Container Load	pcs	14



Strong handle



Shelf as accessory