



PDA3-CTF150B-1

Chilled Display Cabinet

Product Features

- Flat glass top
- LED light under each shelf
- Front glass hinges forward if required
- Temperature Class 3M1
- Excellent product visibility
- Glass rear sliding doors
- Digital controller and temperature display
- Castors
- Easy to clean condenser filter

Refrigerated display counter with flat glass structure

The PDA3-CTF is our high-quality range of pastry displays. With its black finish, glass shelves and LED lighting, in the top of the unit as well as underneath each shelf, it offers a stylish design and product presentation.

The chilled display counter has an efficient ventilated cooling system and temperature class 3M1, ensuring that your food, pastries and cakes are stored under ideal conditions. The temperature is easy to adjust on the digital controller.

The cabinet has sliding doors to the rear for smooth service and loading, while the front glass hinges forward for easy cleaning access. The counter is equipped with castors for mobility.

Measures and Content

| | | |
|--------------------|----------------|-----------|
| Total Display Area | m ² | 2.98 |
| Temperature Range | °C | -1 to +5 |
| Climate Class | | 3 |
| Net Volume | l | 432 |
| Gross Volume | l | 680 |
| Gross / Net Volume | l | 680 / 432 |
| Gross / Net Weight | kg | 320 / 253 |

Design and Material

| | | |
|-----------------------|-------------------------|----------|
| Door Number & Type | 2 sliding glass doors | |
| Tempered glass | | Yes |
| No. of Doors | | 2 |
| No. of Shelves | pcs | 3 |
| Shelf Dimensions | 1416 x 400 mm | |
| Shelves Number & Type | 3 glass shelves + base | |
| Castors | | 4 wheels |
| Interior Light | | LED |
| Exterior Finish | Black/Glass | |
| Interior Finish | Stainless steel / Glass | |

Cooling and Functions

| | | |
|--------------------|---|------------|
| Type of Controller | | Electronic |
| Type of Defrost | | Automatic |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 145 |
| Thermometer | | Yes |

Power and Consumption


| | | |
|---------------------------|----------|------------|
| Energy Class | | B |
| Annual Energy Consumption | kWh/year | 2825 |
| Energy Consumption | kWh/24h | 7.74 |
| EEl | % | 16.9 |
| Input Power | W | 790 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 65 |

Dimensions

| | | |
|----------------------------|-----|-------------------|
| External Dimension (WxDxH) | mm | 1500 x 750 x 1360 |
| Internal Dimension (WxDxH) | mm | 1446 x 600 x 808 |
| Packed Dimension (WxDxH) | mm | 1580 x 820 x 1475 |
| 40ft Container Load | pcs | 15 |



Digital controller



LED light under each shelf