



RF1420X1

Upright Freezer GN2/1

Product Features

- Stainless steel cabinet
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Ventilated cooling
- Self-closing doors
- Adjustable shelves GN2/1
- Pedal for opening the door (self-installation)
- Maintenance free condenser
- Strong wheels
- Lock

2-door stainless steel freezer for professional kitchens

The RF1420X1 is an energy-efficient freezer for professional settings. It has a 64% lower energy consumption compared to the previous RF1420 model.

This upright freezer is made from durable SS304 stainless steel to ensure that it can withstand the conditions of a busy kitchen. It comes with adjustable GN2/1 shelves and the doors have a 105 degree stop for easy access and loading. The cabinet is equipped with strong wheels, which come in handy in terms of cleaning.

It has an efficient ventilated cooling system to ensure that content stays at its optimal storage temperature, and the temperature is easy to set on the digital controller. The controller has NFC connectivity and Bluetooth. This means you can keep an eye on the temperature and humidity of the cabinet via an app, and you can export data for easy reporting for HACCP purposes.

Measures and Content

Gross / Net Weight	kg	234 / 224
Net Volume	l	954
Gross Volume	l	1300
Gross / Net Volume	l	1300 / 954
Temperature Range	°C	-22 to -18
Climate Class		5

Design and Material

Exterior Finish		SS304
Interior Finish		SS304
No. of Doors		2
Door No & Type		2 hinged self-closing solid doors
Door Reversible		Yes
Max load on Shelves	kg/m²	70
No. of Shelves	pcs	6
Shelves No & Type		6 wire shelves grey
Shelf Color		Grey
Shelf Dimensions		530x650
Castors		Castors
Lock		Yes
Interior Light		LED

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, electric
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes

Power and Consumption

Energy Class		B
Annual Energy Cons.	kWh/year	1763
Energy Consumption	kWh/24h	4.83
EEl	%	28.6
Input Power	W	480
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48

Dimensions

External Dimension (WxDxH)	mm	1420 x 875 x 2090
Internal Dimension (WxDxH)	mm	1240 x 700 x 1501
Packed Dimension (WxDxH)	mm	1445 x 905 x 2150
40ft Container Load	pcs	16



Pedal for opening the door



Digital thermostat