

		Model	FAST 80	
		Code Production	FT800	
		Interface :		
				
				
	Overall Dimension (Width-Depth-Height) *open	mm	724 - 818 - 1529(*2010)	
	Packaging Dimension (WxDxH)	mm	760x840x1520	
	Gross weight	Kg	120	
	Net weight	Kg	110	
	Volume	mc	0,98	
	Rack size	mm	500x500	
	Max door /hood opening	mm	450	
	Max glasses/plate Height	mm	425	
	General construction		double skin	
	Door/hood Construction		single skin	
	Tank construction		deep drawn	
	Tank volume	liter	15	
	Tank heating element	W	2.100	
	Tank surface strainers		yes- composite	
	Wash pump type		double flow	
	Wash pump power	W	470	
	Wash temperature	°C	60 (55-->65)	
	Boiler type		pressurized	
	Boiler volume	liter	6	
	Back-flow system		valve	
	Boiler heating element	W	7.000	
	Rinse booster pump		NO	
	Rinse booster pump power	W	-	
	Rinse temperature	°C	80 (67-->88)	
	Rinse water consumption	Liter /rack	2,1	
	Optimal external water pressure	bar	2 - 4	
	Drain system		overflow	
	Drain filter		double filter	
	Drain pump		optional	
	Rinse aid dispenser	peristaltic	YES	
	Detergent dispenser	peristaltic	optional	
	Wash cycle	sec	60 - 90 - 180	
	Special cycle	programs	n°1	
	Self cleaning cycle		yes	
	Electric Power	W	9.600	
	Electric Connection	V - ph - Hz	400V 3N 50Hz	
	Fuse	A	16	
	Plates racks	n° 1	780131	
	Flat Rack	n° 1	780132	
	Cutterly Rack	n° 1	780139	
	Electric cable	n° 1	YES	
	Drain hose	n° 1	YES	
	Fill hose	n° 1	YES	

Installation layout		Hood type		NH50		00			
M.P.UCCI	15.07.2014	Determination:		Code:	Rev.:				
Designed by:	Date:								

