



Trojan T20 FGD EHA

Remote Multideck - Extended Height

Product Features

- Colour is anthracite RAL7016
- Requires remote refrigeration system (not supplied)
- Horizontal LED lighting
- Frameless glass doors for great product visibility
- Adjustable shelves, max weight 160kg/sq metre
- Shelves can be flat or angled to 7° or 14°
- Solid 40 mm endwalls with mirrored interior
- Digital controller and temperature display
- Can be multiplexed with kit (POA)
- EPOS Ticket strips & shelf risers
- Extraction rate 650w/per metre
- Fully automatic, fan assisted cooling

Remote Multideck - Extended Height

A highly useful remote multideck range (at an extended height) that allows you to maximise your display space whilst reducing the impact of noise and heat. Available in 4 sizes. This unit is multiplexable, with a kit, and allows you to create a more extensive display size. Trojans offer a large display area with high-capacity vertical merchandising, great for product presentation. Ideal for an extensive variety of chilled products with even temperature distribution across all shelf levels. Plus the LED illumination enhances the presentation of produce, whilst the energy-efficient operation and modular construction allows for seamless continuous line-ups. Please note this requires an additional remote refrigeration system. 2 year parts warranty only.

Measures and Content

Gross / Net Weight	kg	428 / 405
Gross / Net Volume	l	/
Total Display Area	m²	2.94
Temperature Range	°C	-1 to +5
Climate Class		3

Design and Material

Exterior Finish		Anthracite RAL7016
Interior Finish		Anthracite RAL7016
No. of Doors		4
Door Number & Type		4 hinged glass door
Door Reversible		No
No. of Shelves	pcs	5
Shelves Number & Type		5 adjustable
Shelf Color		Anthracite
Shelf Dimensions		5 x 450 mm
Tempered glass		Yes

Cooling and Functions

Type of Defrost		Automatic
Refrigerant		R449a
Refrigerant Charge	g	REMOTE

Power and Consumption

Energy Class		C
Max Ambient		+25°C, 60% RH
Energy Consumption	kWh/24h	13.67
Annual Energy Consumption	kWh/year	4990
EEL	%	33.2
Voltage / Frequency	V/Hz	220-240/50

Dimensions

External Dimension (WxDxH)	mm	1959 x 784 x 2236
Internal Dimension (WxDxH)	mm	1875 x 450 x 1738
Packed Dimension (WxDxH)	mm	2100 x 850 x 2390
40ft Container Load	pcs	14



Digital controller



Strong handles