

		Model	Fast 50	
		Code Production	917412	
		Interface :		
				
	Overall Dimension (Width-Depth-Height) *open	mm	525x555(895*)x715	
	Packaging Dimension (WxDxH)	mm	640x580x870	
	Gross weight	Kg	49	
	Net weight	Kg	43	
	Volume	mc	0,37	
	Rack size	mm	450x450	
	Max door /hood opening	mm	300	
	Max glasses/plate Height	mm	280/280	
	General construction		single skin	
	Door/hood Construction		double skin	
	Tank construction		welded	
	Tank volume	liter	14	
	Tank heating element	W	600	
	Tank surface strainers		Yes- composite	
	Wash pump type		double flow	
	Wash pump power	W	200	
	Wash temperature	°C	60	
	Boiler type		pressurized	
	Boiler volume	liter	2,6	
	Back-flow system		valve	
	Boiler heating element	W	2.600	
	Rinse booster pump		NO	
	Rinse booster pump power	W	-	
	Rinse temperature	°C	65	
	Rinse water consumption	Liter /rack	1,9	
	Optimal external water pressure	bar	2 - 4	
	Drain system		overflow	
	Drain filter		double filtering	
	Drain pump		optional	
		Rinse aid dispenser	peristaltic	YES
Detergent dispenser		peristaltic	optional	
	Wash cycle	sec	90 - 120	
	Special cycle	programs	-	
	Self cleaning cycle		YES	
	Electric Power	W	3.500	
	Electric Connection	V - ph - Hz	230V 1N 50Hz	
	Fuse	A	16	
	Water softner		NO	
	Plates racks	n°1	780129	
	Flat Rack	n°1	780128	
	Cutterly Rack	n°1	780139	
	Electric cable	n°1	YES	
	Drain hose	n°1	YES	
	Fill hose	n°1	YES	

