



UR600X1

Solid Door Refrigerator

Product Features

- Stainless steel exterior
- Adjustable shelves GN2/1
- Integrated handle
- Fan assisted cooling
- Digital controller and temperature display
- Adjustable feet with rollers to rear
- Lock
- Reversible door (spare parts 72307 + 72305 needed)

Solid door refrigerator with GN2/1 shelves, stainless steel

The UR range of solid door refrigerators from TEFCOLD combines traditional reliability with sleek design. Each unit comes with a practical integrated handle. Designed for demanding foodservice settings, this particular model features adjustable GN2/1 shelves with an impressive load capacity of up to 25 kg per shelf. It has fan-assisted cooling and a digital thermostat for easy temperature control. Note that this particular model is energy-optimized and the energy consumption is 57% lower than that of its predecessor. Available in various colours and sizes, the UR range offers both solid and glass door models. For freezers, see our UF range.

Measures and Content

Gross / Net Weight	kg	97 / 90
Net Volume	l	570
Gross Volume	l	620
Gross / Net Volume	l	620 / 570
Temperature Range	°C	-2 to +8
Climate Class		4

Design and Material

Exterior Finish		SS430
Interior Finish		White
No. of Doors		1
Door type		hinged solid door
Door Number & Type		1 hinged solid door
Door Reversible		
No. of Shelves	pcs	4
Shelves Number & Type		4 wire shelves white
Shelf Color		White
Shelf Dimensions		GN2/1
Bottom Shelf Dimensions	mm	654 x 330
Max load on Shelves	kg/m²	196
Feet / Legs		2 adjustable feet
Castors		2 rollers
Lock		Yes
Interior Light		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Fan assisted
Type of Defrost		Automatic / Off Cycle
Refrigerant		R600a
Refrigerant Charge	g	70
Thermometer		Yes

Power and Consumption

Energy Class		A
Max Ambient		+30°C, 55% RH
Energy Consumption	kWh/24h	0.79
Annual Energy Consumption	kWh/year	288
EEl	%	21.9
Power		13 Amp
Input Power	W	95
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	777 x 735 x 1895
Internal Dimension (WxDxH)	mm	653 x 580 x 1660
Packed Dimension (WxDxH)	mm	840 x 765 x 2100
40ft Container Load	pcs	42



Designed for GN1/1 pans,
not supplied



Strong wheels as option