



CW2

Buffet Display

Product Features

- Static cooling
- Digital controller and temperature display
- Stainless steel construction
- Suitable for building into counters
- Accepts Gastronorm pans (not supplied)
- Accepts GN1/1 pan(s) (not supplied)

A drop-in refrigerated well with static cooling designed to be used with gastronorm pans (available in sizes to take 2, 3, 4 or 5 x 1/1 gastronorm pans). The well features a robust stainless steel construction and is ideal for use with salads or other chilled produce. Please note these units have to be built into a counter (not supplied). It is the purchaser's responsibility to ensure there is a suitable sneeze screen or covers for the purpose it is being used for, and that airflow within the unit is not interrupted and suitable cooling is allowed around the condenser. Incorrect installation will invalidate any warranty. Installation must comply with relevant environmental health and food safety standards.

Measures and Content

Capacity GN Pans	pcs	2 x GN1/1
Temperature Range	°C	+2 to +8
Climate Class		4
Gross / Net Weight	kg	49 / 44
Gross / Net Volume	l	69 / 68

Design and Material

Number of dividers	pcs	3
Exterior Finish		Stainless steel
Interior Finish		Stainless steel

Cooling and Functions


Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	70
Thermometer		Yes

Power and Consumption

Energy Consumption	kWh/24h	2.88
Annual Energy Consumption	kWh/year	1051
Power		13 Amp
Max Ambient		30°C at 55% RH
Input Power	W	122
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	42

Dimensions

Internal Dimension (WxDxH)	mm	660 x 570 x 175
External Dimension (WxDxH)	mm	768 x 678 x 536
Packed Dimension (WxDxH)	mm	820 x 730 x 680
40ft Container Load	pcs	132



Designed for GN1/1 pans, not supplied



Automatic evaporation of defrost water