



RK1420X1

Upright Cooler GN2/1

Product Features

- Stainless steel cabinet
- Adjustable shelves GN2/1
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Self-closing doors with a 105 degree stop
- Ventilated cooling
- Maintenance free condenser
- Strong wheels
- Pedal for opening the door (self-installation)
- Lock

2-door stainless steel cooler for professional kitchens

The RK1420X1 is an energy-efficient cooler for professional settings. It has a 53% lower energy consumption compared to the previous RK1420 model.

This upright cooler is made from durable SS304 stainless steel to ensure that it can withstand the conditions of a busy kitchen. It comes with adjustable GN2/1 shelves and the doors have a 105 degree stop for easy access and loading. The cabinet is equipped with strong wheels, which come in handy in terms of cleaning.

It has an efficient ventilated cooling system to ensure that content stays fresh, and the temperature is easy to set on the digital controller. The controller has NFC connectivity and Bluetooth. This means you can keep an eye on the temperature and humidity of the cabinet via an app, and you can export data for easy reporting.

Measures and Content

Gross / Net Weight	kg	226 / 208
Net Volume	l	954
Gross Volume	l	1300
Gross / Net Volume	l	1300 / 954
Temperature Range	°C	-2 to +8
Climate Class		5

Design and Material

Exterior Finish		SS304
Interior Finish		SS304
No. of Doors		2
Door No & Type		2 hinged self-closing solid doors
Door Reversible		Yes
Max load on Shelves	kg/m²	72.6
No. of Shelves	pcs	6
Shelves No & Type		6 wire shelves grey
Shelf Color		Grey
Shelf Dimensions		GN2/1
Castors		4 castors
Lock		Yes
Interior Light		LED

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic / Off Cycle
Refrigerant		R600a
Refrigerant Charge	g	110
Thermometer		Yes

Power and Consumption

Energy Class		A
Annual Energy Cons.	kWh/year	464
Energy Consumption	kWh/24h	1.27
EEL	%	21.3
Input Power	W	360
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	47

Dimensions

External Dimension (WxDxH)	mm	1420 x 875 x 2090
Internal Dimension (WxDxH)	mm	1240 x 700 x 1501
Packed Dimension (WxDxH)	mm	1445 x 905 x 2150
40ft Container Load	pcs	16



Pedal for opening the door



Digital thermostat