



LHF620SS (ECO DESIGN)

Solid Lid Chest Freezer

Product Features

- Stainless steel lid
- Static cooling
- Defrost drain
- Baskets
- Lock
- Thermometer

Solid Lid Chest Freezer

The LHF SS range of chest freezers offers an ideal storage solution, with a high quality stainless steel lid. With efficient energy use and a temperature range of -16 to -23 °C, this ensures your frozen goods remain in great condition. Equipped with a static cooling system and secure lock, it's easy to both access and maintain. Perfect for reducing operational costs while providing reliable frozen storage for your business. With stainless steel lid and defrost drain as well as additional product features.

Measures and Content

| | | |
|--------------------|----|------------|
| Temperature Range | °C | -23 to -16 |
| Climate Class | | 3 |
| Net Volume | l | 426 |
| Gross Volume | l | 556 |
| Gross / Net Volume | l | 556 / 426 |
| Gross / Net Weight | kg | 82 / 77 |

Design and Material

Door Number & Type

| | | |
|----------------------|------------------------------------|---|
| Lid Number & Type | 1 hinged solid stainless steel lid | |
| Number of lids | | 1 |
| Basket Number & Type | 2 | |
| No. of baskets | pcs | 2 |
| Max No. of Baskets | pcs | 4 |

Exterior Finish White With Stainless Lid

Interior Finish White

Cooling and Functions

| | | |
|--------------------|------------|-----|
| Type of Controller | Mechanical | |
| Type of Defrost | Manual | |
| Refrigerant | R600a | |
| Refrigerant Charge | g | 110 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------------|---------------|------------|
| Energy Class | C | |
| Max Ambient | +25°C, 60% RH | |
| Annual Energy Consumption | kWh/year | 738 |
| Energy Consumption | kWh/24h | 2.02 |
| EEL | % | 30.6 |
| Power | 13 Amp | |
| Input Power | W | 163 |
| Voltage / Frequency | V/Hz | 220-240/50 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| External Dimension (WxDxH) | mm | 1700 x 729 x 861 |
| Internal Dimension (WxDxH) | mm | 1586 x 536 x 696 |
| Packed Dimension (WxDxH) | mm | 1760 x 760 x 940 |
| 40ft Container Load | pcs | 40 |



Digital thermometer



Lock