




CRPF2730

Cold Room

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Easy, economic and effective storage in cold rooms

Measures and Content

Gross / Net Weight	kg	761 / 731
Internal Volume	m ³	14.72
Temperature Range	°C	0 to +8
Wall Thickness	mm	80

Design and Material

Exterior Finish	White	
Interior Finish	White	
Max Load on Floor	kg/m²	1500
No. of Doors		1
Door No & Type	1 hinged solid door W:700 H:1845	
Door Reversible		Yes
Lock		Yes
Interior Light		LED

Cooling and Functions

Type of Controller	Electronic	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	170
Thermometer	Yes	

Power and Consumption


Energy Consumption	kWh/24h	23.4
Annual Energy Cons.	kWh/year	8541
Input Power	W	910
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

External Dimension (WxDxH)	mm	2700 x 3000 x 2200
Internal Dimension (WxDxH)	mm	2540 x 2840 x 2040
Packed Dimension (WxDxH)	mm	2800 x 1900 x 2400
40ft Container Load	pcs	7



Strong handle



Shelf as accessory

Cold rooms are perfect as plug-in with quick and easy assemble.

The cooling unit comes completely pre-mounted in a panel and does not require extra expert knowledge. The interchangeable modular panels even allow varies positioning of both the panel with the cooling unit and the panel with the door.

The cold room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price. Cold rooms are a perfect and easy accessible way to store foods, dairy products and beverages.

The many different cold room sizes give a good fit in most conditions. Cold rooms are available as both cooler and freezer models. Shelves are optional. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the cold room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.