



## TM45C

### Minibar Cooler

#### Product Features

- Low energy consumption
- Compressor operated cooling system
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Adjustable shelves, also in door
- Reversible solid door
- LED interior light
- Integrated handle
- Lock

### Minibar cooler with an exceptional low energy consump

This compressor operated minibar with a solid door is an excellent choice for hotels in warmer surroundings. The cooling system helps secure a lower temperature level as well as a shorter pull-down time compared to absorption operated minibars. It also has some cool programming features. It can be timed, so the compressor only runs when the room is highly likely to be empty, e.g. from 9-12 am and 6-9 pm. This means it is completely silent at other times, when guests are likely in the room. A so-called water-pack maintains the cold temperature in the minibar, when it is running. It also features a SLEEP-mode for forced silence as well as a FAST-cool function for immediate cooling. This is very handy if guests arrive at an odd hour.

#### Measures and Content

Temperature Range	°C	+5 to +10
Climate Class		4
Gross / Net Weight	kg	21 / 20
Gross Volume	l	38
Gross / Net Volume	l	38 / 34

#### Design and Material

Door No & Type		1 hinged solid door
Door Reversible		Yes
Shelves No & Type		2 plastic shelves
Feet / Legs		Adjustable feet
Exterior Finish		Black
Interior Finish		White
Interior Light		LED
Lock		Yes

#### Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Static
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	26
Thermometer		No

#### Power and Consumption

Energy Class		D
Max Ambient		30°C at 55% RH
Energy Consumption	kWh/24h	0.16
Annual Energy Cons.	kWh/year	57
Power Supply		13 Amp
Input Power	W	65
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

#### Dimensions

Internal Dimension (WxDxH)	mm	310 x 300 x 455
External Dimension (WxDxH)	mm	402 x 500 x 565
Packed Dimension (WxDxH)	mm	450 x 535 x 620
40ft Container Load	pcs	330



Integrated handle



Lock