TEFCOLD®
COOL PRODUCTS WORLDWIDE



# CRU7610P w/o Panel

Monoblock Cooler Unit (7.6-10m³)


**Product Features**
- Monoblock cooling unit
- Automatic condensate evaporation
- Ambient temperature up to +43 °C and 65% humidity
- Digital controller and temperature display
- Stainless steel finish
- Fits panels with a thickness of 80-150 mm

| Measures and Content | | |
|---|---|---|
| Gross / Net Weight | kg | 90 / 80 |
| Capacity Cooling Coldroom Units | m³ | 7,6 - 10 |
| Temperature Range | °C | 0 to 8 |
| **Design and Material** | | |
| Exterior Finish | | SS430 |
| **Cooling and Functions** | | |
| Type of Controller | | Electronic |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 150 |
| Thermometer | | Yes |
| **Power and Consumption** | | |
| Energy Consumption | kWh/24h | 21.12 |
| Annual Energy Consumption | kWh/year | 7709 |
| Input Power | W | 1310 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| **Dimensions** | | |
| External Dimension (WxDxH) | mm | 600 x 910 x 880 |
| Packed Dimension (WxDxH) | mm | 700 x 1110 x 1170 |
| 40ft Container Load | pcs | 60 |

## Monoblock cooler unit for temperature -2 to +8 °C

Monoblock cooler unit for cold rooms with a volume of 7.6-10m³.

When installing the monoblock, ensure a minimum distance of 30 cm between the condenser fan (or heat exhaust) and the ceiling. Sufficient ventilation at the installation location is recommended.



Monoblock rear – no panel attached




Digital controller