



Trojan T38 FGD EHA

Remote Multideck - Extended Height

Product Features

- Colour is anthracite RAL7016
- Requires remote refrigeration system (not supplied)
- Horizontal LED lighting
- Frameless glass doors for great product visibility
- Adjustable shelves, max weight 160kg/sq metre
- Shelves can be flat or angled to 7° or 14°
- Solid 40 mm endwalls with mirrored interior
- Digital controller and temperature display
- Can be multiplexed with kit (POA)
- EPOS Ticket strips & shelf risers
- Extraction rate 650w/per metre
- Fully automatic, fan assisted cooling

Remote Multideck - Extended Height

These remote multidecks are a great option for maximising your display space, helping to reduce the impact of both noise and heat. These come at an extended height. Available in 4 sizes. You can multiplex these units, with use of a kit, this allows you to create an even bigger display size. A large display area creates impressive product presentation with high-capacity vertical merchandising. Stock up with a variety of chilled products with even temperature distribution across all shelf levels. Illuminated by LED lighting. This also enhances the display impact, whilst the energy-efficient operation and modular construction allows for seamless continuous line-ups. Important - an additional remote refrigeration system is required. 2 year parts warranty only.

Measures and Content

Gross / Net Weight	kg	750 / 695
Gross / Net Volume	l	/
Total Display Area	m ²	6.03
Temperature Range	°C	-1 to +5
Climate Class		3

Design and Material

Exterior Finish		Anthracite RAL7016
Interior Finish		Anthracite RAL7016
No. of Doors		6
Door Number & Type		6 hinged glass door
Door Reversible		No
No. of Shelves	pcs	5
Shelves Number & Type		5 adjustable
Shelf Color		Anthracite
Shelf Dimensions		5 x 450 mm
Tempered glass		Yes

Cooling and Functions

Type of Defrost		Automatic
Refrigerant		R449a
Refrigerant Charge	g	REMOTE

Power and Consumption

Energy Class		D
Max Ambient		+25°C, 60% RH
Energy Consumption	kWh/24h	27.3
Annual Energy Consumption	kWh/year	9965
EEL	%	37.1
Voltage / Frequency	V/Hz	220-240/50

Dimensions

External Dimension (WxDxH)	mm	3834 x 784 x 2236
Internal Dimension (WxDxH)	mm	3750 x 450 x 1738
Packed Dimension (WxDxH)	mm	4000 x 850 x 2390
40ft Container Load	pcs	6



Digital controller



Strong handles