



## NIC202SC

### Ice Cream Freezer

#### Product Features

- Flat sliding glass lids with lock
- Great branding possibilities
- LED interior light
- Castors with brake
- Digital thermometer
- Powder coated white steel inner liner
- Includes full set of baskets
- Climate class 5 for high performance in warm surroundings

### Elegant chest freezer with flat sliding glass lids

The NIC-SC range is a compact display chest freezer in an elegant design. It has curved corners, rounded edges and flat sliding glass lids.

It is a very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in many sizes, which makes this model perfect for smaller shops and delis with limited space as well as larger shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

It is ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

#### Measures and Content

Temperature Range	°C	-24 to -14
Climate Class		5
Net Volume	l	138
Gross Volume	l	186
Gross / Net Volume	l	186 / 138
Gross / Net Weight	kg	63 / 52

#### Design and Material

Tempered glass		Yes
Number of lids		2
Lid Number & Type		2 flat sliding temp. glass lids
No. of baskets	pcs	2
Basket Number & Type		2 Wire baskets, white
Max No. of Baskets	pcs	2
Castors		4 wheels, 2 with brake
Interior Light		LED
Lock		Yes
Exterior Finish		White
Interior Finish		White painted steel

#### Cooling and Functions

Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R600a
Refrigerant Charge	g	55
Thermometer		Yes

#### Power and Consumption

Energy Class		D
Max Ambient		+40°C, 40% RH
Annual Energy Consumption	kWh/year	440.19
Energy Consumption	kWh/24h	1.206
EEL	%	37.8
Power		13 Amp
Input Power	W	165
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

#### Dimensions

External Dimension (WxDxH)	mm	740 x 650 x 885
Internal Dimension (WxDxH)	mm	600 x 510 x 576
Packed Dimension (WxDxH)	mm	810 x 765 x 940
40ft Container Load	pcs	84



White coated steel inner liner



Illuminated display board as option (accessory)