



BERMUDA VIEW RV10

Ventilated Scoop Ice Cream Display

Product Features

- High vision display (low front glass)
- Perfect temperature distribution
- Heated glass to help prevent condensation
- Suitable for Napoli Pans (not included)
- LED interior light with switch
- Digital controller and temperature display
- Easy access storage compartment
- Rear night curtain to maintain temperature
- Ventilated cooling
- Automatic defrost

Ventilated 13 scoop ice cream display with under-storage

The Bermuda View RV13 ice cream scooping cabinet accommodates 13 Napoli pans. Its ventilated cooling system ensures that your gelato or ice cream is maintained at the perfect serving temperature. In addition, the cabinet is equipped with a separate refrigerated under storage, which enables fast restocking of the display without leaving the unit. The Bermuda View range is all about displaying the ice cream. It therefore has a low front glass for better visibility. The Bermuda model has a sleek curved glass feature that is both practical and elegant and the front glass is heated to help prevent condensation. This unit is equipped with castors for easy mobility and an internal LED light that beautifully illuminates your products. With its exceptional blend of quality and affordability, the Bermuda range has become a popular choice among ice cream and gelato vendors.

Measures and Content

Serving Capacity		10 Napoli pans (5 L)
Storage Capacity (under)		10 Napoli pans (5 L)
Total Display Area	m ²	0.65
Temperature Range	°C	-20 to -14
Climate Class		7
Gross / Net Weight	kg	226 / 195
Gross / Net Volume	l	300 / 255

Design and Material

SneezeGuard	Yes
Tempered glass	Yes
Castors	4 castors
Exterior Finish	White
Interior Finish	White
Interior Light	LED
Lock	No

Cooling and Functions


Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	195
Thermometer	Yes	

Power and Consumption

Energy Class	D	
Max Ambient	35°C at 75% RH	
Energy Consumption	kWh/24h	22
Annual Energy Cons.	kWh/year	8030
Power Supply	13 Amp	
Input Power	W	1250
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	56

Dimensions

Internal Dimension (WxDxH)	mm	1200 x
External Dimension (WxDxH)	mm	1340 x 814 x 1354
Packed Dimension (WxDxH)	mm	1410 x 860 x 1455
40ft Container Load	pcs	16



Strong castors



Easy access storage compartment