



## PC1250B

### Supermarket Multideck Cooler

#### Product Features

- Frameless glass doors for great product visibility
- Low energy consumption
- Black interior and exterior
- Adjustable shelves with tilting function
- LED light under each shelf
- Ventilated cooling for fast pull-down and even temperature
- Digital controller and temperature display
- Glass end walls as standard
- Castors and locking feet
- 33 mm ticket strips with shelf risers included

### Black multideck cooler with frameless glass doors

The PC multideck cooler is all about product visibility and comes with frameless glass doors as well as glass end walls. To further highlight the products, the cooler is equipped with horizontal LED lighting at the top of the cabinet and below each shelf. The 450 mm deep shelves are adjustable and have a tilting function for better product presentation. Front risers are included. The PC is a spacious cooler with a low energy consumption, and you get a good quality for a competitive price. It is temperature class 3M1, which means it is suitable for display of packed fresh meat, dairy products, fresh fruit and vegetables and is ideal for supermarkets, convenience stores, delis or sandwich shops.

#### Measures and Content

Total Display Area	m <sup>2</sup>	3.14
Temperature Range	°C	-1 to +5
Climate Class		3
Gross / Net Weight	kg	300 / 260
Gross / Net Volume	l	1292 / 764

#### Design and Material

Door No & Type	2 hinged glass doors	
Tempered glass	Yes	
Shelves No & Type	5 adjustable	
Shelf Color	Black	
Max load on Shelves	kg/m <sup>2</sup>	160
Feet / Legs	4 adjustable feet	
Castors	4 castors	
Exterior Finish	Black RAL9005	
Interior Finish	Black RAL9005	
Interior Light	LED	

#### Cooling and Functions


Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R290	
Refrigerant Charge	g	149
Thermometer	Yes	

#### Power and Consumption

Energy Class	B	
Energy Consumption	kWh/24h	5.87
Annual Energy Cons.	kWh/year	2143
Input Power	W	550
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	62

#### Dimensions

Internal Dimension (WxDxH)	mm	1250 x 450 x 1540
External Dimension (WxDxH)	mm	1310 x 740 x 2050
Packed Dimension (WxDxH)	mm	1340 x 770 x 2120
40ft Container Load	pcs	25



Display with a button for each feature



LED light under each shelf