



## CRNF1224

Freezer room

### Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Ventilated floor kit as accessory
- Strip curtain included
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble. The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door. The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price. We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks). Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system. Not suitable for outdoor use.

### Measures and Content

Internal Volume	m <sup>3</sup>	4.06
Wall Thickness	mm	120
Insulation Density	kg/m <sup>3</sup>	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	450 / 420
Gross / Net Volume	l	

### Design and Material

Door No & Type	1 hinged solid door W:580 H:1765	
Max Load on Floor	kg/m <sup>2</sup>	2000
Exterior Finish	White	
Interior Finish	White	
Interior Light	LED	
Lock	Yes	

### Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	150
Thermometer	Yes	

### Power and Consumption

Max Ambient	40°C at 40% RH	
Energy Consumption	kWh/24h	22.49
Annual Energy Cons.	kWh/year	8208
Power Supply	13 Amp	
Input Power	W	1100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

### Dimensions

Internal Dimension (WxDxH)	mm	960 x 2160 x 1960
External Dimension (WxDxH)	mm	1200 x 2400 x 2200
Packed Dimension (WxDxH)	mm	2400 x 1320 x 2400
40ft Container Load	pcs	8



Strong handle



Shelf as accessory