



CRNF1821

Coldroom (Freezing)

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Strip curtain included
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Measures and Content

| | | |
|--------------------|----------------|------------|
| Wall Thickness | mm | 120 |
| Internal Volume | m ³ | 5.69 |
| Temperature Range | °C | -20 to -10 |
| Gross / Net Weight | kg | 655 / 615 |

Design and Material

| | | |
|--------------------|----------------------------------|------|
| Door Number & Type | 1 hinged solid door W:700 H:1765 | |
| No. of Doors | 1 | |
| Max Load on Floor | kg/m ² | 2000 |
| Interior Light | LED | |
| Lock | Yes | |
| Exterior Finish | White | |
| Interior Finish | White | |

Cooling and Functions

| | | |
|--------------------|--------------------|-----|
| Type of Controller | Electronic | |
| Type of Defrost | Automatic, hot gas | |
| Refrigerant | R290 | |
| Refrigerant Charge | g | 150 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------------|----------|------------|
| Annual Energy Consumption | kWh/year | 9864 |
| Energy Consumption | kWh/24h | 27.02 |
| Power | 13 Amp | |
| Input Power | W | 1510 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 60 |

Dimensions

| | | |
|----------------------------|-----|--------------------|
| External Dimension (WxDxH) | mm | 1800 x 2100 x 2200 |
| Internal Dimension (WxDxH) | mm | 1560 x 1860 x 1960 |
| Packed Dimension (WxDxH) | mm | 2150 x 1250 x 2400 |
| 40ft Container Load | pcs | 12 |



Strong handle



Shelf as accessory