



## Trojan T14 FGD EHA

Remote Multideck - Extended Height

### Product Features

- Colour is anthracite RAL7016
- Requires remote refrigeration system (not supplied)
- Horizontal LED lighting
- Frameless glass doors for great product visibility
- Adjustable shelves, max weight 160kg/sq metre
- Shelves can be flat or angled to 7° or 14°
- Solid 40 mm endwalls with mirrored interior
- Digital controller and temperature display
- Can be multiplexed with kit (POA)
- EPOS Ticket strips & shelf risers
- Extraction rate 650w/per metre
- Fully automatic, fan assisted cooling

Remote Multideck - Extended Height

A great remote multideck option at an extended height is ideal for maximising your display space and product visibility whilst reducing the impact of heat and noise. Available in 4 sizes. This unit is multiplexable with a kit to allow you to create a bigger display size. It requires an additional remote refrigeration system. Trojans offers a large display area with high-capacity vertical merchandising. Ideal for an extensive range of chilled products with even temperature distribution across all shelving levels. What's more the LED illumination enhances product presentation, whilst the energy-efficient operation and modular construction allows for seamless continuous line-ups. 2 year parts warranty only.

### Measures and Content

Gross / Net Weight	kg	303 / 285
Gross / Net Volume	l	/
Total Display Area	m <sup>2</sup>	2.01
Temperature Range	°C	-1 to +5
Climate Class		3

### Design and Material

Exterior Finish		Anthracite RAL7016
Interior Finish		Anthracite RAL7016
No. of Doors		2
Door Number & Type		2 hinged glass door
Door Reversible		No
No. of Shelves	pcs	5
Shelves Number & Type		5 adjustable
Shelf Color		Anthracite
Shelf Dimensions		5 x 450 mm
Tempered glass		Yes

### Cooling and Functions

Type of Defrost		Automatic
Refrigerant		R449a
Refrigerant Charge	g	REMOTE

### Power and Consumption

Energy Class		C
Max Ambient		+25°C, 60% RH
Energy Consumption	kWh/24h	9
Annual Energy Consumption	kWh/year	3285
EEl	%	28.6
Voltage / Frequency	V/Hz	220-240/50

### Dimensions

External Dimension (WxDxH)	mm	1250 x 784 x 2236
Internal Dimension (WxDxH)	mm	1250 x 450 x 1738
Packed Dimension (WxDxH)	mm	1450 x 850 x 2390
40ft Container Load	pcs	22



Digital controller



Strong handles