

COOL PRODUCTS WORLDWIDE



LGF5000 BLACK

Glass Door Display Freezer

Product Features

- · Fully automatic, fan assisted cooling
- Adjustable shelves
- Castors and locking feet
- Self closing doors with stay open feature for ease of loading
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- Light canopy with switch
- Heated glass door to prevent condensation
- Internal stainless steel base

The TEFCOLD LGF5000 now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also an LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

Measures and Content		
Total Display Area	m²	1.38
Temperature Range	°C	-25 to -14
Climate Class		4
Gross / Net Weight	kg	244 / 210
Gross / Net Volume	I	1108 /
Design and Material		
Door Number & Type		2 hinged glass doors
Shelves Number & Type		8
Exterior Finish		Black
Interior Finish		Black
Interior Light		2 x Vertically LED in door frame
Cooling and Functions		
Type of Cooling		Ventilated
Type of Defrost		Automatic, electrical
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes
Power and Consumption		
Energy Class		С
Energy Consumption	kWh/24h	12.77
Annual Energy Consumption	kWh/year	4660
Power		13 Amp
Max Ambient		30°C at 55% RH
Input Power	W	1200
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	61
Dimensions		
Internal Dimension (WxDxH)	mm	1262 x 640 x 1520
External Dimension (WxDxH)	mm	1382 x 800 x 2055
Packed Dimension (WxDxH)	mm	1430 x 860 x 2180
40ft Container Load	pcs	22





Illuminated canopy

Strong castors