





ELEGANCE 13

Scoop Ice Cream Display

Product Features


- Fully automatic
- Curved glass canopy
- Static cooling
- Accepts Napoli pans (not supplied)
- LED interior light with switch
- Easy access understorage
- Digital controller and temperature display
- Rear night curtain to maintain temperature
- Castors

13 scoop static cooled display with understorage

Introducing the Elegance, a quality static cooled ice cream scooping display from ISA. With its contemporary flat glass design, this stylish cabinet adds a touch of elegance to any ice cream parlour, cafe or shop. The unit comes in either 10 or 13 scoop options to showcase a tempting variety of flavours. To back this up, the unit has an equivalent number of pans under the main display for tempering, and more in the frozen under storage accessed from the rear door. The unit comes with LED lighting, a rear curtain to help maintain temperature when you are not serving, hinged front glass to simplify cleaning and castors. The large front panel is ideal for personalising with your brand to attract passing customers.

| Measures and Content | | |
|----------------------------|----------|----------------------|
| Serving Capacity | | 13 Napoli Pans (5 L) |
| Storage capacity (under) | | 14 Napoli pans (5 L) |
| Total Display Area | m² | 0.77 |
| Temperature Range | °C | -15 to -12 |
| Climate Class | | 7 |
| Gross / Net Weight | kg | 228 / 218 |
| Gross / Net Volume | 1 | |
| Design and Material | | |
| Tempered glass | | Yes |
| Castors | | Castors |
| Exterior Finish | | White |
| Interior Finish | | Painted Steel |
| Interior Light | | LED |
| Cooling and Functions | | |
| Type of Cooling | | Static |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 148 + 32 |
| Power and Consumption | | |
| Energy Class | | C |
| Energy Consumption | kWh/24h | 12.23 |
| Annual Energy Consumption | kWh/year | 4464 |
| Power | | 13 Amp |
| Max Ambient | | 35°C at 75% RH |
| Input Power | W | 825 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | 1500 x 520 x |
| External Dimension (WxDxH) | mm | 1647 x 980 x 1340 |
| Packed Dimension (WxDxH) | mm | 1749 x 978 x 1450 |
| 40ft Container Load | pcs | 13 |
| | | |







Frame hinges forward for easy cleaning