



PDC126 VS SL LED

Black impulse cooler

Product Features

- Energy saving variable speed compressor
- Plexi glass sides for great product visibility
- Impressive storage space
- Tilting function for better product display
- LED interior light
- 4 solid castors, 2 with brakes
- Bumper bars on 4 sides
- Maintenance free condenser

Energy efficient impulse cooler with glass lids

The PDC impulse cooler is all about showcasing the products inside. It has clear plexi glass on all four sides as well as easy sliding glass lids on the top. Furthermore, it comes with two horizontal LED light strips. This provides a fantastic product visibility no matter from which direction the customer sees it. If the cooler is placed against a wall, it can be tilted 15 degrees for a better product display. The island cooler has a variable speed compressor as well as highly efficient EC fans, allowing for a more silent and energy efficient operation. This is a unique feature for this kind of product. The unit is easy to move with tubular 360 degree bumper bars as well as strong casters with brakes. That way you can always relocate it to wherever the need is biggest in your store. In terms of maintenance, the impulse cooler has a maintenance free condenser as well as a stainless steel bottom plate to ensure easy cleaning.

Measures and Content

| | | |
|--------------------|----------------|-----------|
| Total Display Area | m ² | 1.51 |
| Temperature Range | °C | -1 to +5 |
| Climate Class | | 3 |
| Gross / Net Weight | kg | 176 / 133 |
| Gross Volume | l | 408 |
| Gross / Net Volume | l | 408 / 190 |

Design and Material

| | | |
|-----------------|----------------------------|--|
| Lid No & Type | 2 curved sliding glass lid | |
| Castors | 4 wheels, 2 with brake | |
| Exterior Finish | Black / Glass | |
| Interior Finish | Stainless steel / Glass | |
| Interior Light | 2 x Vertically LED | |
| Lock | No | |

Cooling and Functions

| | | |
|--------------------|---------------------|-----|
| Type of Controller | Electronic | |
| Type of Cooling | Ventilated | |
| Type of Defrost | Automatic-Off Cycle | |
| Refrigerant | R290 | |
| Refrigerant Charge | g | 150 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------|----------------|------------|
| Energy Class | D | |
| Max Ambient | 25°C at 60% RH | |
| Energy Consumption | kWh/24h | 5.25 |
| Annual Energy Cons. | kWh/year | 1916 |
| Power | 13 Amp | |
| Input Power | W | 700 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 52 |

Dimensions

| | | |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm | 1210 x 1080 x 342 |
| External Dimension (WxDxH) | mm | 1405 x 1210 x 1005 |
| Packed Dimension (WxDxH) | mm | 1335 x 1170 x 1140 |
| 40ft Container Load | pcs | 36 |



Sliding glass lids



LED light