



NIC402SC-SO

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Flat sliding glass lids with lock
- Great branding possibilities
- LED interior light
- Castors with brake
- Digital thermometer
- Powder coated white steel inner liner
- Optional - Scooping baskets for plastic tubs
- Climate class 5 for high performance in warm surroundings

Static scoop ice cream freezer

The NIC-SC-SO ice cream freezer offers a stylish design at an affordable price. It has a rounded top trim, curved corners and a curved glass top for a nice product presentation, while sliding lids keep the energy consumption to a minimum when not serving. The scoop freezer is equipped with LED lighting in the front, making sure your ice cream flavors are always nicely illuminated. The NIC-SC-SO comes with strong castors for mobility.

Be aware that the freezer comes with standard baskets, but if you need baskets suitable for 5 l scoop ice cream tubs, these are available as options. Type and number must be ordered under accessories. These baskets are suitable for 5 l plastic tubs - Napoli pans will not fit in there.

Ideal baskets for scoop ice

- For 5L plastic tubs: 2x item no. 14705 + 1x 14707 (10x 5L)
- For 4L plastic tubs: 6x item no. 21286 (12x 4L)

Measures and Content

Gross / Net Weight	kg	110 / 91
Serving Capacity	10 Plastic Tubs (5L) / 12 Plastic Tubs (4L)	
Storage Capacity (under)	19 Plastic Tubs (5L) / 19 Plastic Tubs (4L)	
Temperature Range	°C	-24 to -14
Climate Class	5	

Design and Material

Exterior Finish	White	
Interior Finish	White painted steel	
Tempered glass	Yes	
Castors	4 wheels, 2 with brake	
Lock	Yes	
Interior Light	LED	

Cooling and Functions

Type of Controller	Mechanical	
Type of Cooling	Static	
Type of Defrost	Manual	
Refrigerant	R290	
Refrigerant Charge	g	105
Thermometer	Yes	

Power and Consumption

Energy Class	D	
Max Ambient	+40°C, 40% RH	
Energy Consumption	kWh/24h	1.992
Annual Energy Cons.	kWh/year	727.08
EEL	%	43.6
Power Supply	13 Amp	
Input Power	W	225
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	1320 x 650 x 885
Packed Dimension (WxDxH)	mm	1400 x 760 x 855
40ft Container Load	pcs	50



Scooping basket option



Castors with and without brake