



MILLENNIUM ST24

Ventilated Scoop Ice Cream Display

Product Features


- Great product visibility
- Flat glass top
- Accepts Napoli pans (not supplied)
- LED interior light with switch
- Digital controller and temperature display
- Front glass hinges forward if required
- Double glazed glass on sides
- Heated glass to help prevent condensation

Professional 24 scoop ventilated ice cream display with

The Millennium ST24 ice cream display cabinet is the epitome of luxury for discerning ice cream retailers. This 24 napoli pan display is designed to showcase your ice cream in the most impressive way possible. Contemporary flat glass that is heated to reduce minimise condensation, the display creates a stunning visual appeal, while the efficient, ventilated cooling system keeps your ice cream or gelato at the perfect serving temperature, ensuring that it remains fresh and delicious Plus, the rear features a pull-down night curtain to maintain cabinet temperature during slower periods and the front glass hinges forwards to make cleaning easier. If you're looking for a high-end scooping display cabinet that truly sets you apart, the Millennium ST24 is the ideal choice.

| Measures and Content | | |
|----------------------------|--------------|-------------------------|
| Serving Capacity | | 24 Napoli Pans (5 L) |
| Storage capacity (under) | | No Under Storage |
| Total Display Area | m² | 1.43 |
| Temperature Range | °C | -20 to -14 |
| Climate Class | | 7 |
| Gross / Net Weight | kg | 478 / 412 |
| Gross / Net Volume | 1 | 1300 / 241 |
| Design and Material | | |
| Exterior Finish | | White |
| Interior Finish | | Stainless steel |
| Interior Light | | LED |
| Cooling and Functions | | |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 2 x 148 |
| Thermometer | | Yes |
| Power and Consumption | | |
| Energy Class | | D |
| Energy Consumption | kWh/24h | 34 |
| Annual Energy Consumption | kWh/year | 12410 |
| Power | 16 Amp Singl | e Phase Commando Socket |
| Max Ambient | | 35°C at 75% RH |
| Input Power | W | 2640 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 58 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | |
| External Dimension (WxDxH) | mm | 2156 x 1054 x 1356 |
| Packed Dimension (WxDxH) | mm | 2300 x 1550 x 1620 |
| 40ft Container Load | pcs | 10 |







Heated front glass