



## GVC33-140 S/S

Vitrine Cooler GN1/4

### Product Features

- Stainless steel lid
- Stainless steel
- Accepts GN1/4 pan(s) (not supplied)
- Digital controller and temperature display
- Static cooling
- Adjustable feet

### Refrigerated stainless steel topping unit with lid

The GVC is designed to meet the demands of fast-paced food service. Whether you're running a pizzeria, fast-food restaurant, or sandwich shop, this vitrine cooler makes food prep easier, ensuring everything you need is organized and within reach. The topping unit accepts gastronorm pans (not included) – see the technical specifications for more information about the capacity of this specific unit. The GVC maintains optimal temperatures with a reliable static cooling system. This keeps your ingredients fresh and ready to use, while the manual defrost feature prevents ice build-up for hassle-free operation. Constructed from durable SS201 stainless steel, the topping shelf is built to last. It is equipped with a stainless steel lid, saving energy and protecting your ingredients. Perfect for businesses where speed and quality are essential, the GVC is designed to optimize your food prep process.

### Measures and Content

|                    |     |           |
|--------------------|-----|-----------|
| Capacity GN Pans   | pcs | 6 x GN1/4 |
| Temperature Range  | °C  | +2 to +8  |
| Climate Class      |     | 4         |
| Gross / Net Weight | kg  | 31.5 / 27 |
| Gross / Net Volume | l   | 38.5 / 31 |

### Design and Material

|                 |  |                 |
|-----------------|--|-----------------|
| Lid No & Type   |  |                 |
| Feet / Legs     |  | Adjustable feet |
| Exterior Finish |  | SS201           |
| Interior Finish |  | SS201           |
| Interior Light  |  | No              |

### Cooling and Functions

|                    |   |            |
|--------------------|---|------------|
| Type of Controller |   | Electronic |
| Type of Cooling    |   | Static     |
| Type of Defrost    |   | Manual     |
| Refrigerant        |   | R600a      |
| Refrigerant Charge | g | 45         |
| Thermometer        |   | Yes        |

### Power and Consumption

|                     |          |                |
|---------------------|----------|----------------|
| Max Ambient         |          | 30°C at 55% RH |
| Energy Consumption  | kWh/24h  | 2.64           |
| Annual Energy Cons. | kWh/year | 964            |
| Power Supply        |          | 13 Amp         |
| Input Power         | W        | 110            |
| Voltage / Frequency | V/Hz     | 220-240/50     |
| Noise Level         | dB(A)    | 40             |

### Dimensions

|                            |     |                    |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm  | 1050 x 245 x 150   |
| External Dimension (WxDxH) | mm  | 1400 x 335 x 288.5 |
| Packed Dimension (WxDxH)   | mm  | 1500 x 375 x 330   |
| 40ft Container Load        | pcs | 270                |



Accepts GN1/4 pan(s)  
(not supplied)



Stainless steel lid for  
protection of food