



CK7410X1SP

Gastronorm Counter

Product Features

- Fully automatic
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Adjustable shelves
- Self-closing doors
- High quality catering grade 304 stainless steel
- Accepts Gastronorm pans (not supplied)
- Splashback
- 1/1 Gastronorm cupboards
- Castors, 2 lockable
- Replaceable door gasket

Stainless steel counter chiller with GN1/1 shelves

The CK7410X1SP is made for professional kitchens, and it offers an ideal solution for keeping ingredients chilled and within easy reach during service. It has a 54% lower energy consumption compared to its predecessor. It is made from durable SS304 stainless steel and features automatic defrost and GN1/1 dimensioned shelves for easy cleaning and smooth workflows. The legs are adjustable, so it is possible to adapt the height of the table to your needs. Its ventilated cooling system keeps contents at a consistent temperature, and the electronic controller makes it easy to adjust the temperature to fit your ingredients. The controller has NFC connectivity and Bluetooth. This means that you via an app can control the lighting, check the temperature of the cabinet, and even export data for easy reporting. It has a tabletop with splash back, which can be removed if you wish to use it as an undercounter chiller and add your own tabletop.

Measures and Content

Temperature Range	°C	-2 to +8
Climate Class		5
Gross / Net Weight	kg	184 / 174
Gross / Net Volume	l	616 / 393

Design and Material

Door Number & Type		4 hinged self-closing doors
Shelves Number & Type		4 wire shelves grey
Shelf Color		Grey
Max load on Shelves	kg/m ²	13
Feet / Legs		6 adjustable legs
Exterior Finish		SS304
Interior Finish		SS304
Lock		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Charge	g	95
Thermometer		Yes

Power and Consumption

Energy Class		A
Energy Consumption	kWh/24h	1.82
Annual Energy Consumption	kWh/year	664
Power		13 Amp
Input Power	W	300
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	38

Dimensions

Internal Dimension (WxDxH)	mm	1669 x 580 x 564
External Dimension (WxDxH)	mm	2230 x 700 x 960
Packed Dimension (WxDxH)	mm	2260 x 730 x 1010
40ft Container Load	pcs	32



GN1/1 shelves



Drawers available as separate kit