



UR600X1

Storage Cooler GN2/1

Product Features

- Lock
- Adjustable shelves GN2/1
- Digital controller and temperature display
- Fan assisted cooling
- Stainless steel exterior
- Integrated handle
- Adjustable feet with rollers to rear
- Reversible door (spare parts 72307 + 72305 needed)

1-door storage cooler with GN2/1 shelves, stainless steel

The TEFCOLD UR is a classic storage cooler that combines time-tested reliability with a clean design, featuring a practical integrated handle. This particular model boasts an impressively low energy consumption, which is 57% lower than its predecessor.

Ideal for demanding foodservice environments, this refrigerated cabinet comes with adjustable GN2/1 shelves with a remarkable load capacity of up to 25 kg per shelf. The storage fridge has fan-assisted cooling, and the temperature is easy to set on a digital thermostat.

The UR range is available in various colors and sizes, and you can choose between solid door- or glass door models. See the UF range for freezer options.

Measures and Content

Gross / Net Weight	kg	97 / 90
Net Volume	l	570
Gross Volume	l	620
Gross / Net Volume	l	620 / 570
Temperature Range	°C	-2 to +8
Climate Class		4

Design and Material

Exterior Finish		SS430
Interior Finish		White
No. of Doors		1
Door Type		hinged solid door
Door No & Type		1 hinged solid door
Door Reversible		No
No. of Shelves	pcs	4
Shelves No & Type		4 wire shelves white
Shelf Color		White
Shelf Dimensions		GN2/1
Bottom Shelf Dimensions	mm	654 x 330
Max load on Shelves	kg/m ²	196
Feet / Legs		2 adjustable feet
Castors		2 rollers
Lock		Yes
Interior Light		No

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Fan assisted
Type of Defrost		Automatic / Off Cycle
Refrigerant		R600a
Refrigerant Charge	g	70
Thermometer		Yes

Power and Consumption

Energy Class		A
Max Ambient		+30°C, 55% RH
Max Running Amps		0,7
Energy Consumption	kWh/24h	0.79
Annual Energy Cons.	kWh/year	288
EEl	%	21.9
Power Supply		13 Amp
Input Power	W	95
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	777 x 735 x 1895
Internal Dimension (WxDxH)	mm	653 x 580 x 1660
Packed Dimension (WxDxH)	mm	840 x 765 x 2100
40ft Container Load	pcs	42



Designed for GN1/1 pans,
not supplied



Strong castors as option